

POWERING THE GREEN REVOLUTION

Stationary storage products and solutions



ABOUT US

Cygni is India's leading energy storage solutions company with over 125,000 batteries deployed so far across mobility and stationary storage. Our 4.8GWh automated gigafactory offers cost competitive, quality products ranging from small scale residential to C&I and grid scale multi MWh solutions.




ESS USE CASES

Cygni's BESS systems can support six unique use cases with significant cost benefits to end users.

 Buffered EV charging


 Store renewables

 Back up power

 Peak saving


 Energy shifting

 Grid ancillary services




DG ABATEMENT WITH CYGNI

Cygni's BESS systems can be synchronised to work with existing DG and Solar PV to minimize consumption of diesel.




AC-COUPLED

This configuration is suitable for systems where Solar is already installed. AC coupling makes it easier to integrate batteries through a compatible PCS and MV transformer.



DC-COUPLED

This is a more cost effective and energy efficient solution where a new Solar plant is planned but size of storage is typically less than 1 MWh.



CYGNI 5MWh DC BLOCK

Cygni's 5MWh DC block is a modular solution for deploying multi MWh storage assets for both behind the meter or generation side storage. It is compatible with many leading PCS models and offers reliable 0.5P i.e. 2.5MW power back up operation for 2 hours.



Better Temperature Control

The liquid cooling scheme keeps cell temperature difference less than 3°C



Superior safety

NFPA 855, UL 9540, UL9540A and UL1973 certifications



Low auxiliary Power Consumption

Optimized liquid cooling channel with efficient compressor for lower aux power consumption



Higher Energy Density

Liquid-cooled energy storage container provides high energy density, and saving costs.

Specifications

DC Side

Cell Type	LFP 314Ah Prismatic
PACK	104.48 kWh / 104S X 1PS
Battery System	5.016MWh/416Sx12P
Voltage Range	1165~1498 Vdc
Rated Voltage	1331.2 Vdc

AC Side

Rated Power	2.5MW
Max. Power	2.5 MVA
THDi	≤ 3%
DC Ratio	0.5%lpn
Nominal Voltage	690 Vac
Power Factor	-1 lagging ~ 1 leading
Nominal Frequency	50 Hz/60 Hz

General

Efficiency	≥ 96%
Charge/Discharge Rate	0.5 P
Cycle Life	≥ 9,000 cycles
Ramp up / down time	100ms
Connectivity	Ethernet/RS485
Ingress Rating	IP55
Cooling	Chiller + liquid cooling
Operating Temperature	-25°C~55°C
Humidity	0-95%RH. non-condensing
Noise	80 dB
Altitude	≤ 2,000m (derating above 2,000m)
Certifications	NFPA 855, UL 9540A, UL 9540, UL 1973
Dimensions (W*D*H)	6058*2,550*2,896 (mm)
Weight	< 45 tons

CYGNI 6.25MWh DC BLOCK

The next generation of higher energy density BESS solution from Cygni with 6.25MWh capacity and ability to support 0.5P operation. Save costs with a smaller area footprint, reduced auxiliary consumption and lower balance of plant costs.



Better Temperature Control

The liquid cooling scheme keeps cell temperature difference less than 3°C



NFPA 855, UL 9540, UL9540A and UL1973 certifications



Low auxiliary Power Consumption

Optimized liquid cooling channel with efficient compressor for lower aux power consumption



Higher Energy Density

Liquid-cooled energy storage container provides high energy density, and saving costs.

Specifications

DC Side

Cell Type	LFP 587Ah Prismatic cell
PACK	195.3kWh / 104S x 1P
Battery System	6.25MWh / 416S x 8P
Voltage Range	1165~1498 Vdc
Rated Voltage	1331.2 Vdc

AC Side

Rated Power	3.1MW
Max. Power	3.1MVA
THDi	≤ 3%
DC Ratio	0.5%lpn
Nominal Voltage	690Vac
Power Factor	-1 lagging -1 leading
Nominal Frequency	50 Hz/60 Hz

General

Efficiency	≥ 96%
Charge/Discharge Rate	0.5 P
Cycle Life	≥ 9,000 cycles
Ramp up / down time	100ms
Connectivity	Ethernet/RS485
Ingress Rating	IP55
Cooling	Liquid cooling
Operating Temperature	-25°C-55°C
Humidity	0-95%RH. non-condensing
Noise	80 dB
Altitude	≤ 2,000m (derating above 2,000m)
Certifications	NFPA 855, UL 9540A, UL 9540, UL 1973
Dimensions (W*D*H)	6058 * 2550 * 2896 (mm)
Weight	< 55 tons

125KW / 261KWH CABINET

Compact, modular and scalable solution with in-built storage and power conversion. Optimal for medium sized requirements where capacity needs to be upgraded in a phased manner. Scalable up to 1MW / 2MWh BESS through parallel configuration.

125kW | 261kWh TO 750kW | 1.5MWh



Modular design

Compact design for efficient and flexible space utilization



Liquid cooling design for > 8000 cycles

High efficiency liquid cooling design to prolong battery life and optimal thermal management



Cutting edge safety

Smoke detection, fire detection, aerosol based fire fighting, water extinguisher support



Fully certified for end use

UL9540A, UL9540, UL1973, UN38.3



Specifications

DC Side

Cell Type	LFP 314Ah prismatic cell
PACK	52.24KWh/52Sx1P
Battery System	261KWh/260Sx1P
Voltage Range	715Vdc~953Vdc
Rated Voltage	832Vdc

PCS specifications

Rated Power	125kW
Max. Power	137.5kVA
THDi	≤ 3%
DC Ratio	0.5% pn
Nominal Voltage	400 Vac
Power Factor	-1 lagging -1 leading
Nominal Frequency	50 Hz/ 60Hz

General

Efficiency	≥ 92%
Charge/Discharge Rate	0.5 P
Cycle Life	≥ 8,000 times
Ramp up / down time	100ms
Connectivity	Ethernet/RS485
Cabinet IP rating	IP55
Cooling	Liquid cooling
Operating Temperature	-25°C~55°C
Humidity	0-95%RH. non-condensing
Noise	65dB
Altitude	≤ 2,000m (derating above 2,000m)
Fire Safety	Aerosol, fire detection, smoke detection, water sprinklers
Dimensions (W*D*H)	1000 x 1350 x 2380 (mm)
Weight	< 2.7 tons

CYGNI 51.2KWH SOLUTION

Cygni's modular design for smaller capacities from 50kWh to 250kWh which supports 1C operation. Ideal for small C&I applications, godowns, villas etc

51.2kWh | 750kWh



Scalable, modular design

Standard 51.2V 100Ah LFP module based design which can be ramped up to 250kWh



Safe and Reliable

Thermal runaway resistant module design for safe operation



Ultra-Long Life

Simple but robust design with design life of up to 15 years



Smart management with EMS

Get full control and cloud connectivity of the BESS with a robust EMS



Specifications

MODEL	MODEL 1	MODEL 2	MODEL 3	MODEL 4	MODEL 5
	CYG-HVPC-25-51.2	CYG-HVPC-50-102.4	CYG-HVPC-75-153.6	CYG-HVPC-100-204.8	CYG-HVPC-125-256
Battery Type / Module	LFP/5.12KWh Module				
Number of battery modules	10 (10S*1Rack)	20 (10S*2Rack)	30 (10S*3Rack)	40 (10S*4Rack)	50 (10S*5Rack)
Battery total energy	51.2KWh	102.4KWh	153.6KWh	204.8KWh	256KWh
Rated capacity	100AH	200AH	300AH	400AH	500AH
Standard Charge/Discharge Power	25KW	50KW	75KW	100KW	125KW
Nominal Voltage	512V				
Operating Voltage	448 - 576V				
Weight (kg) Including Rack	520Kg	1040Kg	1560Kg	2080Kg	2600Kg
Dimensions (WxDXH)	544X555X2250mm	544X555X2250mm X 2	544X555X2250mm X 3	544X555X2250mm X 4	544X555X2250mm X 5
Cooling	Force Air cooled				
Operating temperature	Charge: 0°C ~ +50°C / Discharge: -10°C ~ +55°C				
Installation	Floor Rack mount				
BMS Monitoring Parameters	SOC, System Voltage, Current, Cell Voltage, Cell Temperature,				
Communication cable	RS485, CAN				
Warranty	5 Years				
Certification	IEC-62619, UN-38.3				
The system can be expanded	up to 750 kWh				

SMALL SCALE STORAGE UP TO 40KWH

Simple, modular and low voltage designs for smaller requirements up to 5kWh. Possible to use along with Solar or UPS as a lead acid replacement.

5kWh | 40kWh



UPS and Hybrid inverter compatible

Compatible with popular inverter and UPS makes with plug and play operation



Safe LFP based design

100Ah LFP cells with international safety certifications



Ultra-Long Life

Design of 15 years, can reach upto 5000 cycles



Modular design

Simple 51.2V 100Ah module based design that allows capacity upgrades as needed



Specifications

MODEL	MODEL 1	MODEL 2	MODEL 3	MODEL 4	MODEL 5
	CYG-LVPC-3-5	CYG-LVPC-10-20	CYG-LVPC-10-20	CYG-LVPC-15-30	CYG-LVPC-20-40
Battery Type / Module	LFP/ 51.2KWh				
Number of battery modules	1	2	4	6	8
Battery total energy	5.12kWh	10.24kWh	20.48kWh	30.72kWh	40.96kWh
Rated capacity	100Ah	200Ah	400Ah	600Ah	800Ah
Standard Charge Discharge Power	3KW	5KW	10KW	15KW	20KW
Nominal Voltage	51.2V				
Operating Voltage	44.8-57.6V				
Weight (kg) Including Rack	52	104	210	320	420
Module Dimensions (WDXH)	482X553X133.5mm				
Dimensions (WDXH)	544X555X 225mm	544X555X 410mm	544X555X 820mm	544X555X 1350mm	544X555X 1800mm
Cooling	Natural				
Operating temperature	Charge: 0°C~+50°C/ Discharge: -10°C~+50°C				
Installation	Floor Rack mount				
BMS Monitoring Parameters	SOC, System Voltage, Current, Cell Voltage, Cell Temperature,				
Communication cable	RS485, CAN				
Warranty:	5 Years				
Certification	IEC-62619, UN-38.3				

RESIDENTIAL WALL MOUNTED STORAGE

Compact, efficient and space saving design for residential and small offices.
Save electricity bills and easily integrate with your solar panel. Multiple hybrid inverter models supported.



Flexible and Compatible

5.12kWh modular design,
support 1-4 parallel



Easy Installation

Wall mounted/floor mounted,
save installation



Safe operation and easy to install

Child proof components and smart BMS
with CAN communication for easy
remote monitoring



Maintenance free design

Long life and maintenance free design for
operating up to 15 years




Specifications

Parameter	Specification
Battery Module	CYG-WM-5
Cell Type	LFP
Nominal Voltage	51.2V
Nominal Rating of Module	51.2V, 100 Ah
Rated Energy	5.12kWh to 20.48kWh (up to 4 modules in parallel)
Operating Voltage Range	44.8V to 57.6V
Standard Charging Current	30A
Standard Discharging Current	30A
Max Charging Current	100A (continuous)
Max Discharging Current	100A (continuous)
Charging Temperature Range	0 deg * C to 55 deg * C
Discharging Temperature Range	- 20 deg * C to 60 deg * C
Cooling	Passive
Weight	Use +/- symbol instead of 'plus/minus'
Dimensions (HWD)	623 * 402 * 162mm
Communication Ports	RS485 (* 2) CAN (x1), RS232 (x1)

General

Dimensions	590*510*177 (mm)
Weight	50kg
Communication	CAN/RS485
Installation	Floor/Wall Hanging
Operating Temperature	Change: -5~50°C; Discharge: -20~50°C; Recommended: 15~35°C
Operating Altitude	<= 2,000m
Scalability	Up to 20kWh





MAKE IN INDIA

Contact:

1800 1030314

Address:

Cygni Energy Pvt Ltd,
Survey No.306, Plot No.5,
EMC Maheshwaram Industrial Area,
Maheshwaram, Hyderabad-501 359, India

Email Address:

info@cygni.com